

SPECIFICATION FOR APPROVAL

CUSTOMER

CUS. CODE

CUS. MODEL

HJ-Tech CODE

3D0402BK02-009

PRO. NAME

RF ANTENNA ASSEMBLY

SPECIFICATION
DESCRIPTION

4G EXTERNAL ANTENNA, HOUSING BLACK, RG178
CABLE+SMA PLUG, OD10*L137mm

DATE

2026. 09. 02

SUPPLIER		
PREPARER	CHECKER	APPROVER
S. He	XIU HE	LFY

CUSTOMER		
TRANSCTOR	CHECKER	APPROVER

DONGGUAN HUANGJIE COMMUNICATION TECHNOLOGY CO., LTD.

Address: Daqiandi Industrial Zone, Quantang, Liaobu
Town, Dongguan City, Guangdong Province, China

Tel: 86-769-83328111


Fax: 86-769-83327688

EMAIL: info@iphone-line.com

Website: www.iphone-line.com

CONTENTS

S/N	SYNOPSIS	PAGE
1	COVER	1
2	CONTENTS	2
3	PRODUCT DRAWING	3
4	PRODUCT SPECIFICATION	4~5
5	PACKAGE DRAWING	6
6	ANTENNA ELECTRICAL CHARACTERISTIC TEST REPORT	7~11



REV.	RELEASE AND CHANGE SUMMARY	DATE
A	First Release	2025.06.11

Technical Requirements

1. Electrical Characteristics: 100% tested by Vector Network Analyzer, waveform comparison from 500MHz to 3 GHz.

Characteristic Impedance: 5Ω; Operating Frequency: 824-960 MHz; 1710-1990 MHz; 2300-2700 MHz.

2. Dimension Inspection:

[t] - FAI First-Article Inspection item; - QIP Key Inspection item; * - CPK Process-controlled item.

3. Visual Inspection: 100% visual inspection. No scratches, damage or dirt on product surface; plating shall be bright and uniform without oxidation.

4. Packaging Specification: 50PCS per bag, 700 PCS per carton (35 x 35 x 12 CM).

5. Environmental Requirement The product and all materials used in the manufacturing process shall comply with EU RoHS+HF Halogen-free directives.

8	2YP092	PCB: 47.70 × 5.00 × 1.00 mm, FR 4, Double sided Board, OSP surface finish	1
7	2YG011	Copper Tube: Ø5.00 × L23.00 × Ø1.55 mm, Brass, Raw Material	1
6	2SBKD48N0	Ultra short Lower Fixing Base: Ø9.35 × L14.40 × Ø5.10 mm, Rivet free Structure, PC+PBT, Black	1
5	2SBKU30N1	Upper Fixing Base: Ø10.0 × L20.90 mm, PC+PBT, Black	1
4	2SBKG0400	Sleeve Shaft: Ø10.00 × L104.00 mm, TPEE, Black	1
3	2LC15PM804-5	SMA Contact Pin: Ø1.50 × L10.20 mm, Brass, Gold plated	1
2	2LC15PM808-8	SMA Plug: Ø10.00 × L16.60 mm, Brass, Nickel plated, POM Housing, Black	1
1	2C5R17811BN1	Micro Coaxial Cable: RG178, Silver tinned Conductor, Transparent Brown	1
No.	PART NUMBER	PART NAME AND DESCRIPTION	Q'TY

BOM

GENERAL TOLERANCE: UNLESS OTHERWISE SPECIFIED LINEAR: 0.5 < L ≤ 6 ± 0.05 6 < L ≤ 30 ± 0.10 30 < L ≤ 120 ± 0.20 ANGULAR: 0 < L ≤ 10 ± 1°30' 10 < L ≤ 50 ± 1°00' 50 < L ≤ 120 ± 0°30'		FILE TYPE: Product Drawing		Dongguan HUANGJIE Communication Technology Co., Ltd. 东莞市皇捷通讯科技有限公司			
		DRA./DATE: S.He 25.06.11		TITLE: Product Description			
		CHE./DATE:		Direct.: Connect External Antenna, Model CD417, Black, Copper Tube + PCB, SMA Male Plug with Male Pin plus RG178 Cable, Marking "R 4G" on Upper Fixing Base, Overall Length L=131 mm			
		APP./DATE:		CODE: 3D0402BK02-009			
FILE FORM: HJ-QR-E-03 22.09.01		SIZE: A4	UNIT: mm	PRO.: 3rd		SCALE: 1:1	PAGE: 1/1

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO HUANGJIE AND SHOULDN'T BE USED WITHOUT WRITTEN PERMISSION.



WIFI 2.4G&5.8G EXTERNAL ANTENNA

1 SCOPE

1.1 CONTENTS

This specification covers the performance, tests and acceptance criteria for the EXTERNAL ANTENNA.

1.2 QUALIFICATION

When tests are performed the specification shall be used. All inspections shall be performed using the applicable inspection plan and product drawing.

2 APPLICABLE DOCUMENTS AND FORMS

The associated product documents and forms constitute a part of this specification to the extent specified herein. Unless otherwise indicated, the latest edition of the document applies. In the event of conflict between the requirements of this specification and the product drawing, the product drawing shall take precedence. In the event of conflict between the requirements of the specification and the reference documents, this specification shall take precedence.

3 TEST AND ACCEPTANCE REQUIREMENTS

3.1 GENERAL

3.1.1 Dimensional Characteristics

Part construction shall conform to the dimensions, shape, and detail attributes specified on the latest revision of the applicable part drawing(s).

3.1.2 Material Characteristics

All material used in each test sample shall conform to the material specifications shown on the latest revision of the applicable part drawing(s).

3.2 RATING

Frequency Range	Nominal Impedance	VSWR	Peak Gain	Operating Temperature
4G	50Ω	3.0MAX.	3dBi	-40°C ~ +85°C

3.3 TEST CONDITION

Unless otherwise specified, all tests and measurements shall be performed under the following conditions.

Temperature	Atmospheric Pressure	Relative Humidity
+15°C ~ +35°C	866hPa ~ 1066hPa	45% ~ 75%


3.4 Electrical Performance

No.	Items	Test Condition	Specifications
GENERAL			
1	Contact Resistance	Solder the receptacle connector to the test board and mate the plug connector together, then measure the contact resistance as shown in figure 1 by the four terminal method. Open circuit voltage: 20mV MAX Circuit current: 10mA MAX	Inner contact: Initial: 20mΩ MAX After: 25mΩ MAX Ground contact: Initial: 20mΩ MAX After: 25mΩ MAX
2	Insulation Resistance	Mate the plug and receptacle connector Together, and then, apply DC 200 V Voltage between the inner contact and the ground contact in accordance with EIA 364-21F	Initial: 500 MΩ MIN After: 100 MΩ MIN
3	Dielectric Withstanding Voltage	Mate the plug and receptacle connector together, and then apply AC 300 V between the inner contact and the ground contact in accordance with EIA 364-20F	No flashover, No sparkover, No excess leakage, No breakdown
4	V.S.W.R	Measure V.S.W.R with a network analyzer from 0 to 6GHz	1.8MAX.
MECHANICAL			
5	Un-mating Force	Solder the receptacle to the test board and mate the plug into it. Test the withdrawal force with an insertion-extraction force tester at a rate of 25 ± 3 mm/min	>10kgf
6	Durability	Solder the receptacle onto the test board, interlock the male and female connectors using a mating tester for 500 cycles, and then test the parameters.	Appearance: No AbnormalityConta


			ct Resistance: Shall meet 3.4.1/2/3/4
7	Bending test	1 he antenna should have a good rhythm, when it was bended。 2.When the antenna was fixed ,turn it to 45° angle ,and the antenna didn't slide free。 3.After 200 bending cycles from 45° to 90°, there shall be no powder residue on the fixed base, and no damage to the antenna body.	After testing, the antenna shall maintain good elasticity and be able to hold its position at a 45° angle. Shall meet 3.4.1/2/3/4
ENVIRONMENTAL 环境性能			
8	Humidity	Apply the following environment to themating connector in accordance with EIA364-31 Method III Test Condition B Temperature:25~65°C Humidity : 90~95% R.H Duration: 96 hours	Appearance: No damage Contact Resistance: Shall meet 3.4.1 Insulation Resistance: Shall meet 3.4.2 Dielectric Withstanding Voltage: Shall meet 3.4.3
9	High Tempera-ture Test	Apply the following environment to themating connector Temperature : 90±2°C Duration : 96 hours	Appearance: No damage Contact Resistance: Shall meet 3.4.1 Insulation Resistance: Shall meet 3.4.2 Dielectric Withstanding Voltage: Shall meet 3.4.3
10	Thermal Shock	Perform the following test conditions on mated connectors in accordance with Test Method III, Condition B of EIA-364-32: Temperature: -55°C to 85°C Transfer time: 5 min max. Number of cycles: 5	Appearance: No damage Contact Resistance: Shall meet 3.4.1 Insulation Resistance: Shall meet 3.4.2 Dielectric Withstanding Voltage: Shall meet 3.4.3
11	Salt Spray	EIA 364-26 Test Condition A Apply the following environment to the mating connector Temperature : 35±2°C Relative Humidity : 90~98%R.H Salt water density: 5±1% Duration : 48 hours	Appearance: No damage Contact Resistance: Shall meet 3.4.1

3.5 CHANGE LOG


Revision	Release and Change Summary	Date	Tabulator	Checker	Approver
A		2026.09.02	S.He	XIU HE	LFY



REV.	RELEASE AND CHANGE SUMMARY	DATE
A	FIRST ISSUE	2024.02.28



PACKAGING SPECIFICATION:
1. 50PCS/BAG.
2. ATTACH MATERIAL CARD/ENVIRONMENTAL LABEL TO EACH PE BAG.
3. 1000PCS/BOX(360*360*145),CHOOSE THE APPROPRIATE SIZE OF CARDBOARD BOX
ACCORDING TO THE QUANTITY OF MATERIALS.
4. CARTON SEALING TREATMENT.



GENERAL TOLERANCE: UNLESS OTHERWISE SPECIFIED LINEAR: 0.5 < L ≤ 6 ± 0.05 6 < L ≤ 30 ± 0.10 30 < L ≤ 120 ± 0.20 ANGULAR: 0 < L ≤ 10 ± 1°30' 10 < L ≤ 50 ± 1°00' 50 < L ≤ 120 ± 0°30'	FILE TYPE: PACKING DRAWING	Dongguan HUANGJIE Communication Technology Co., Ltd. 东莞市皇捷通讯科技有限公司			
	DRA./DATE: S.He 24.02.28	TITLE: PACKAGING SPECIFICATION			
	CHE./DATE:	CODE: 3D0402BK02-009			
	APP./DATE:	SIZE: A4	UNIT: mm	PRO.: 3rd	SCALE: 1:1
FILE FORM: HJ-QR-E-03 22.09.01		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO HUANGJIE AND SHOULDN'T BE USED WITHOUT WRITTEN PERMISSION.		PAGE: 1/1	




Antenna Electrical Characteristic Test Report

文件编号:HJ-QR-Q-22 Rev:A0

Part Number:	3D0402BK02-009	Item	Spec	Judge
Part Name:	4G EXTERNAL ANTENNA,HOUSING BLACK,RG178 CABLE+SMA PLUG,OD10*L137mm	VSWR	≤ 3.0	pass
Test Equipment	Agilent E5071C/OTA Chamber	Characteristic impedance	50 Ω	pass
Q uantity	5pcs			
Test Date	2026/9/2			



1 RETURN LOSS



Checker: XIU HE

Tester: S.He




DONGGUAN HUANGJIE COMMUNICATION TECHNOLOGY CO., LTD.

Antenna Electrical Characteristic Test Report

文件编号:HJ-QR-Q-22 Rev:A0

Part Number:	3D0402BK02-009	Item	Spec	Judge
Part Name:	4G EXTERNAL ANTENNA,HOUSING BLACK,RG178 CABLE+SMA PLUG,OD10*L137mm	VSWR	≤ 3.0	pass
Test Equipment	Agilent E5071C/OTA Chamber	Characteristic impedance	50 Ω	pass
Q uantity	5pcs			
Test Date	2026/9/2			

2 VSWR



Checker: XIU HE


Tester: S.He

Antenna Electrical Characteristic Test Report

文件编号:HJ-QR-Q-22 Rev:A0

Part Number:	3D0402BK02-009	Item	Spec	Judge
Part Name:	4G EXTERNAL ANTENNA,HOUSING BLACK,RG178 CABLE+SMA PLUG,OD10*L137mm	VSWR	≤ 3.0	pass
Test Equipment	Agilent E5071C/OTA Chamber	Characteristic impedance	50 Ω	pass
Q uantity	5pcs			
Test Date	2026/9/2			

3 SMITH(R+JX)



Checker: XIU HE

Tester:


S.He

Antenna Electrical Characteristic Test Report

DOC NO.:HJ-QR-Q-22 Rev:A0


Part Number:	3D0402BK02-009	Item	Spec	Judge
Part Name:	4G EXTERNAL ANTENNA,HOUSING BLACK,RG178 CABLE+SMA PLUG,OD10*L137mm	Gian	≤3.0	pass
Test Equipment	Agilent E5071C/OTA Chamber	Characteristic impedance	50Ω	pass
Q uantity	5pcs			
Test Date	2026/9/2			

4 2D/3D RADIATION PATTERN



序号	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
频率(MHz)	700.0	725.0	750.0	775.0	800.0	825.0	850.0	875.0	900.0	925.0	950.0	975.0	1000.0	1710.0	1755.0	1800.0	1845.0	1890.0	1935.0	1980.0
效率(dBi)	-5.29	-5.71	-4.55	-4.91	-3.49	-2.66	-2.88	-2.04	-2.33	-2.15	-2.19	-3.03	-3.14	-2.60	-2.52	-2.36	-2.06	-2.10	-2.23	-2.63
增益(dBi)	-2.91	-2.52	-0.79	0.07	1.38	-0.12	0.94	2.47	3.01	2.46	2.24	1.36	2.29	3.01	3.66	3.02	4.28	3.59	2.44	0.40
效率(%)	29.60	26.86	35.08	32.25	44.82	54.14	51.58	62.56	58.42	61.02	60.33	49.82	48.55	54.98	56.04	58.14	62.26	61.67	59.80	54.60
方向性(dBi)	2.38	3.19	3.76	4.98	4.86	2.55	3.81	4.51	5.34	4.60	4.43	4.39	5.43	5.61	6.17	5.38	6.34	5.69	4.67	3.03
最大增益位置(theta)	153.00	158.00	157.00	163.00	166.00	128.00	153.00	151.00	148.00	147.00	151.00	157.00	151.00	140.00	136.00	129.00	144.00	145.00	152.00	149.00
最大增益位置(phi)	204.00	10.00	357.00	349.00	270.00	180.00	189.00	198.00	191.00	194.00	208.00	342.00	352.00	22.00	30.00	35.00	25.00	24.00	147.00	150.00
水平极化效率(%)	16.76	14.36	18.32	20.77	26.35	28.19	31.82	37.22	29.40	37.82	46.74	32.91	28.20	36.97	42.07	43.12	47.19	48.52	46.52	44.54
垂直极化效率(%)	12.85	12.50	16.76	11.48	18.47	25.95	19.76	25.34	29.02	23.20	13.59	16.92	20.35	18.01	13.97	15.01	15.07	13.15	13.27	10.06
上半球效率(%)	9.37	9.31	12.01	8.67	11.54	14.99	16.86	23.90	19.70	18.68	22.17	20.59	18.21	16.74	17.39	19.27	20.95	24.03	24.14	26.55
下半球效率(%)	20.23	17.55	23.07	23.57	33.27	39.16	34.72	38.67	38.72	42.35	38.16	29.23	30.34	38.24	38.65	38.86	41.31	37.64	35.65	28.04

21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36
2025.0	2070.0	2115.0	2160.0	2205.0	2250.0	2295.0	2340.0	2385.0	2430.0	2475.0	2520.0	2565.0	2610.0	2655.0	2700.0
-2.54	-2.47	-2.86	-3.16	-3.04	-2.60	-2.94	-2.45	-2.32	-2.11	-1.89	-2.42	-3.20	-4.97	-9.11	-12.99
-0.10	-0.35	-1.26	-0.94	-0.15	0.73	0.30	-0.27	0.10	0.13	0.24	-0.49	-1.86	-2.73	-6.12	-9.31
55.67	56.66	51.78	48.28	49.64	54.98	50.85	56.95	58.65	61.46	64.67	57.31	47.84	31.85	12.28	5.03
2.44	2.12	1.60	2.22	2.89	3.33	3.24	2.18	2.42	2.25	2.13	1.93	1.35	2.24	2.99	3.67
140.00	138.00	95.00	58.00	59.00	58.00	62.00	62.00	96.00	72.00	73.00	97.00	97.00	98.00	99.00	99.00
45.00	48.00	154.00	93.00	90.00	87.00	90.00	89.00	38.00	2.00	1.00	40.00	39.00	37.00	34.00	32.00
49.68	51.25	46.60	44.26	45.44	51.07	48.12	54.84	56.31	59.32	62.39	54.82	45.75	30.09	11.17	4.16
5.99	5.41	5.18	4.02	4.20	3.91	2.73	2.11	2.34	2.14	2.28	2.49	2.10	1.77	1.11	0.86
29.51	28.27	27.33	26.43	26.43	29.16	29.02	32.88	32.15	35.18	36.06	30.68	25.36	15.88	6.05	2.41
26.16	28.38	24.45	21.85	23.21	25.81	21.83	24.06	26.50	26.28	28.60	26.63	22.48	15.97	6.23	2.62



Checker: XIU HE

Tester:


S.HE

Antenna Electrical Characteristic Test Report

DOC NO.:HJ-QR-Q-22 Rev:A0

Part Number:	3D0402BK02-009	Item	Spec	Judge
Part Name:	4G EXTERNAL ANTENNA,HOUSING BLACK,RG178 CABLE+SMA PLUG,OD10*L137mm	Gian	3DBI	pass
Test Equipment	Agilent E5071C/OTA Chamber	Characteristic impedance	50Ω	pass
Q uantity	5pcs			
Test Date	2026/9/2			

4 2D/3D RADIATION PATTERN



Checker: XIU HE

Tester:

S.He